

# VFI25/VFI30

## **VENTED** GAS FIREPLACE INSERT

# The Ultimate in Design, Engineering & Quality

elletterererer elle

This unit illustrated is a VFI30 Vented Fireplace Insert – Natural Gas, with V30S2640B Surround Deluxe – Black V30T2640P Trim Polish Brass, V2R2640 Riser for Deluxe Surround VI30GBL Grills – Black and LOGC6 Log Set – Five Piece Cast Split Oak with Glowing Ember Chunks, VI30RL Refractory Brick Liner.

# The Ultimate in Vented Fireplace Inserts, convert your wood burning fireplace to gas.


MODEL HI/LO FIRE CONTROL	VFI25 YES	VFI30 YES
INPUT MAX. (NG)	25,000-17,000 BTU	30,000-17,500 BTU
INPUT MAX. (LP)	25,000-17,000 BTU	30,000-24,000 BTU
EFFICIENCY	74%NG / 78%LP	78%NG / 81%LP
VENTING	4"	4 "
FE (P.4.1-02)	45.8%NG / 45.8%LP	50.6%NG / 50.6%LP


К


L

M

Ν







(4 Piece)

VFI25 SURROUND DIMENSIONS (4 PIECE)

Part #

V25PF3838B

385/8"

1.3<sup>1</sup>/8"

611/16

385/8'

Part #

V25PF2637B

26<sup>1</sup>/2"

5<sup>7</sup>/8"

2"

37'

VFI25 Picture Frame Surround 0

Surround (3 Piece)

#### **3 PIECE SURROUND DIMENSIONS**

MODELS	Height (O)	Width (P)	Part #
FLAT			
VFI25	21″	29″	V25S2129B
VFI25	27 <sup>1</sup> /4″	383/4"	V25S2738B
VFI30	27 <sup>3</sup> /4″		V30S2740B
VFI30	303/4"	44"	V30S3044B
DELUXE		·	·
VFI25	24 <sup>13</sup> /16″	36 <sup>3</sup> /16"	V25S2436B
VFI30	26 <sup>13</sup> /16″	40 <sup>3</sup> /4"	V30S2640B
DELUXE LARGE			
VFI25	26 <sup>13</sup> /16″	403/16"	V25S2640B
VFI30	28 <sup>13</sup> /16"	44 <sup>3</sup> /4"	V30S2844B

#### MINIMUM SIZE FOR INSTALLATION

MODELS	Front Width	Rear Width	Height	Depth
VFI25	24″	20 <sup>1</sup> /2"	17 <sup>1</sup> /2	16″
VFI30	29″	20 <sup>1</sup> /2"	20 <sup>3</sup> /4	16 <sup>1</sup> /2″

### FEATURES\*

- Millivolt valve system allows operation during a power failure with Hi/low heat and flame adjustment
- Blower with a thermostat controlled on/off including variable speed control is standard on all models
- Spill Safety Switch in case of a blocked flue or downdraft, it will shut down the unit
- Dual burner system with glowing embers
- Bedroom and Bed Sitting Room approved

### **OPTIONAL FEATURES\***

Log Sets - Choose from our LOGC6 five piece cast split oak log set with glowing ember chunks, or LOGC5 four piece cast split oak or LOGF5 four piece fibre split oak

Grills - Grills available in Black, Polish Brass, Antique Brass, Chrome and Classic Series Black with Polish Brass, Antique and Chrome Accents

Surrounds (3 piece) - Black with Polish Brass, Antique or Chrome Trim

Panel Kit - Antique Brass, Chrome or Polish Brass (not available for Deluxe surrounds)

Picture Frame (4 piece) -

VFI25 only - Black with Polish Brass, Antique or Chrome Trim

**Risers for Deluxe Surrounds** – Increases height coverage by 21/2"

Thermostat - Wall Mount Millivolt, Thermostat, or Programmable Thermostat

Remote Control - On/Off, Thermostat or Hi/Lo On/Off **Refractory Brick Liner – VFI30 only** 

## CHOICE OF LOG SETS

#### LOGC5 Split Cast Log Set

This unit illustrated is a VFI30 Vented Fireplace Insert – Natural Gas, with V30S2640B Surround Deluxe – Black V30T2640P Trim Polish Brass, V2R2640 Riser for Deluxe Surround VI30GBL Grills - Black and LOGC5 Split Cast Log Set, VI30RL Refractory Brick Liner.



Kingsman Industries maintains a program of continuous testing, refinement and improvements of all its products. Some aspect of units shown here may be changed at any time without notice or obligation.

Certification: The models VFI25 and VFI30 are certified for Canada and USA. Listed Vented Gas Fired Room Heater to CANI-21-M86, CAN/CGA 2.17-M91, ANSI 221.11.1a-1993, CR89-001, CGAP.4-1-1996, ANSI 221.50-1996/CGA 2.22-M96. \*Components may have to be ordered separately to create a complete unit. Discuss with your local Kingsman dealer for clarification.





07/08

2340 Logan Avenue Winnipeg, Manitoba, Canada R2R 2V3 Phone: (204) 632-1962 Fax: (204) 632-1960 www.kingsmanfireplaces.com